



Port-A-Lite®

PAL 1000 / PAL 2000

135,500 TO 271,000 TOTAL LUMENS

10 FT. TO 12 FT.

MAXIMUM ADJUSTABLE HEIGHT



SINCE 1938

Reliability, Performance and Integrity.

Port-A-Lite®

PAL 1000 / PAL 2000

Compact and powerful, the Port-A-Lite® series provide the portable lighting needed to produce the highest quality work in concrete finishing, paving, masonry, roofing, excavation, mining, refineries, quarries, demolition, training sites, and special events. The PAL 2000W4 / PAL 2500W4 features a built-in pad for a portable generator so it can be used where utility power is not available. Models available in 120 V 60 Hz (with 1,250 W lamp) or 220 V 50 Hz (with 1,000 W lamp).



KEY FEATURES

- SHO-HD® Lamp Fixtures
- Illuminates Five Times More Area than a 1,000 Watt Quartz Light
- Welded Steel Frame
- 10" Diameter Wheels
- Caster Brakes - PAL 2000W2/PAL 2500W4
- Winch Actuated Mast - PAL 2000W2/PAL 2500W4
- Frosted Lens

WHY ALLMAND®

When it comes to managing a jobsite, you want equipment that will not fail you when you need it most. You're looking for trust and reliability. Allmand® brings that to your jobsite, with over 75 years of respected experience. Our focus on Service and Support allows users to get the parts, technical service and support they need. Product innovation has helped us develop state-of-the-art towable jobsite equipment, bringing portable light towers, mobile industrial heaters, flashing arrow boards, portable light stands, portable air compressors and mobile generators for the construction, mining, oil & gas, and rental markets.

Frequency	50 Hz		60 Hz	
Model	PAL 1000W2	PAL 2000W4	PAL 1250W2	PAL 2500W4
Number of Luminaries	1	2	1	2
Wattage	1,000 W	2,000 W	1,250 W	2,500 W
Light Type	Metal Halide SHO-HD® fixture			
Lumens - Total	135,500	271,000	135,500	271,000
Operating Voltage	220 V		120 V	
Operating Amperage	4.5 A	2 x 4.5 A	10.0 A	2 x 10.0 A
Plug Type	Schuko Type E/F (CEE7/7)	(2) Schuko Type E/F (CEE7/7)	3-Wire Grounded (NEMA 5-15P)	(2) 3-Wire Grounded (NEMA 5-15P)
Height - Mast Raised	10.1 ft (3.1 m)	12.0 ft (3.7 m)	10.1 ft (3.1 m)	12.0 ft (3.7 m)
Height - Mast Lowered	6.6 ft (2.0 m)	8.0 ft (2.4 m)	6.6 ft (2.0 m)	8.0 ft (2.4 m)
Width - Overall	24.7 in (627 mm)	44.8 in (1,138 mm)	24.7 in (627 mm)	44.8 in (1,138 mm)
Weight	115 lbs (52.2 kg)	310 lbs (140.6 kg)	115 lbs (52.2 kg)	310 lbs (140.6 kg)
Operating Weight	106 lbs (48.1 kg)	229 lbs (103.9 kg)	106 lbs (48.1 kg)	229 lbs (103.9 kg)

Allmand has a policy of continuous product improvement and reserves the right to modify its specifications at any time and without prior notice.



Holdrege, Nebraska 68949
 P: (800) 562-1373 • F: (308) 995-5887
www.allmand.com

SINCE 1938