

HYDROSTATIC TEST PUMPS



HAND OPERATED HYDROSTATIC TEST PUMPS

Ideal for testing residential water lines. Also for pressure testing small pressure tanks, sprinkler, boiler and solar systems. Lightweight and easy to use. $\frac{3}{4}$ " garden hose female inlet and $\frac{9}{16}$ "- 18 JICF male outlet. Equipped with shut off valve, gauge, and adjustable internal relief valve. 10 foot output hose included.

29200 300 psi/21 bar (pictured), Shipping weight.....12 lbs. (5.5kg)

29201 1000 psi/70 bar, Shipping weight12 lbs. (5.5kg)

Accessories:

- 3915 10' High-Pressure Output Hose ($\frac{3}{8}$ " NPT male output connection)
- 29250 Pump Rebuild Kit
- 34550 10' Long Suction Hose with strainer ($\frac{3}{4}$ " male garden hose connection)

29900 HYDROSTATIC TEST PUMP

Designed especially for use in heating, compressed air, refrigeration systems, oil installations and sprinkler systems. Complete with 2.6 gallon stainless steel integral tank and 10 ft. output hose.

Specifications: 870 psi/60 bar, $\frac{1}{2}$ " connections

Shipping weight.....17 lbs. (8kg)

Accessories:

- 3915 10' High-Pressure Output Hose
- 29950 Pump Repair Kit





GAS POWER OPERATED HYDROSTATIC TEST PUMPS

Ideal for certifying the integrity of newly installed or repaired water lines, sewer lines, commercial sprinkler systems, and pressure vessels. All gasoline driven models come with Briggs & Stratton™ Intek Pro or Honda engines and are backed by their warranties. Recirculating systems provide pump protection and water conservation. Carts are wheeled for ease of movement. All units come standard with 10 ft. high-pressure output hose and 10 ft. suction hose with strainer.

46301 ROLLER PUMP

Features: 5.4 gpm/300 psi (20.5 lpm/21 bar), 6.5 hp. B&S engine.

Shipping weight.....132 lbs. (60kg)

463010 Same as 46301 except with 5.5 hp. Honda engine.....129 lbs. (59kg)

36352 Pump Repair Kit for both Models



46453 TWIN PISTON PUMP

Features: 10 gpm/400 psi (38 lpm/28 bar), 6.5 hp. B&S engine.

Shipping weight.....160 lbs. (73kg)

464530 Same as 46453 except with 5.5 hp. Honda engine.....160 lbs. (73kg)

36351 Pump Repair Kit for both Models



36454 TWIN PISTON TEST PUMP

Features: 10 gpm/400 psi (38 lpm/28 bar), 6.5 hp. B&S engine. Comes complete with 10 ft. high pressure output hose and 10 ft. suction hose with strainer. Features roll cage instead of cart with wheels.

Shipping weight.....135 lbs. (61.5kg)

364540 Same as 36454 except with 5.5 hp. Honda engine.....136 lbs. (62kg)

36351 Pump Repair Kit for both Models



46200 TRIPLEX PLUNGER PUMP

Features: 3.5 gpm/1200 psi (13 lpm/84 bar), 6.5 hp. B&S engine.

Shipping weight.....130 lbs. (59kg)

462000 Same as 46200 except with 5.5 hp. Honda engine.....130 lbs. (59kg)

Accessories for Both Models:

34052 Discharge Valve Kit

34053 Pump Seal Kit



46501 TRIPLE DIAPHRAGM PUMP ...CAPABLE OF HANDLING 10% CHLORINE SOLUTIONS

Features: 10 gpm/500 psi (37.8 lpm/35 bar), 6.5 hp. B&S engine

Shipping weight.....136 lbs. (62kg)

465010 Same as 46501 except with 5.5 hp. Honda engine.....136 lbs. (62kg)

36345 Pump Repair Kit for both Models

36349 Pump Repair Kit for Models 46500 and 465000

Wheeled pumps are available with cages. Contact factory for details and pricing.

HYDROSTATIC TEST PUMPS

CONTINUED



46701 TRIPLE DIAPHRAGM PUMP WITH TANK

...CAPABLE OF HANDLING 10% CHLORINE SOLUTIONS

- 46701 Same as 46501 with pressure feed tank.....Shipping weights: 203 lbs. (92.5kg)
 467010 Same as 465010 with pressure feed tank.....203 lbs. (92.5kg)
 36345 Repair Kit for both Models
 36349 Pump Repair Kit for Models 46700 and 467000



46600 DIAPHRAGM PUMP

...CAPABLE OF HANDLING 10% CHLORINE SOLUTIONS

- Features: 15 gpm/300 psi (57 lpm/21 bar), 6.5 hp. B&S engine
 Shipping weight.....136 lbs. (62kg)

- 466000** Same as 46600 except with 5.5 hp. Honda engine.....136 lbs. (62kg)
 36347 Pump Repair Kit for both Models



46800 DIAPHRAGM PUMP

...CAPABLE OF HANDLING 10% CHLORINE SOLUTIONS

- Features: 26 gpm/250 psi (90 lpm/17.5 bar), 8 hp. B&S engine
 Shipping weight.....230 lbs. (104.5kg)

- 468000** Same as 46800 except with 8 hp. Honda engine.....233 lbs. (106kg)
 36390 Pump Repair Kit for both Models




ELECTRIC POWERED HYDROSTATIC TEST PUMPS

The following units come standard with a 10 ft. high-pressure output hose.

39300 ELECTRIC HYDROSTATIC TEST PUMP

The ideal pump for certifying fire sprinkler lines, as well as commercial plumbing and industrial testing. Compact and lightweight for portability, yet powerful and rugged for professional use. Built-in adjustable pressure regulator.

- Features: 4 gpm/300 psi (15 lpm/20 bar) 1/2 hp., 115/230V, 60Hz Motor.
 Shipping weight.....35 lbs. (16kg)
 39350 Pump Repair Kit



35100 TWIN PISTON PUMP

- Features: 3 gpm/500 psi (11 lpm/35 bar) 1 hp. capacitor start motor, 115/230V, single phase, 60Hz.
 Shipping weight.....91 lbs. (41.5kg)
 36361 Pump Repair Kit

35101 TWIN PISTON PUMP

- Features: 3 gpm/500 psi (11 lpm/35 bar) 1 hp. capacitor start motor, 220V, single phase, 50Hz.
 Shipping weight.....91 lbs. (41.5kg)
 36361 Pump Repair Kit



33100 TRIPLEX PLUNGER PUMP

- Features: 1 gpm/1000 psi (7 lpm/70 bar) 1 hp. capacitor start motor, 115/230V, single phase, 60Hz.
 Shipping weight.....87 lbs. (39.5kg)
 36389 Pump Repair Kit

33101 TRIPLEX PLUNGER PUMP

- Features: 1 gpm/1000 psi (7 lpm/70 bar) 1 hp. capacitor start motor, 220V, single phase, 50Hz.
 Shipping weight.....87 lbs. (39.5kg)
 36389 Pump Repair Kit



ELECTRIC DIRECT DRIVE TRIPLEX PLUNGER PUMPS

Features: single phase 1.5 hp., 15 amp. capacitor start motor

47100	2.2 gpm/1000 psi (10 lpm/70 bar) 115V, 60Hz	96 lbs.	(44kg)
47101	2.2 gpm/1000 psi (10 lpm/70 bar) 220V, 50Hz	96 lbs.	(44kg)
47102	1.1 gpm/2000 psi (5 lpm/138 bar) 115V, 60Hz	96 lbs.	(44kg)
47103	1.1 gpm/2000 psi (5 lpm/138 bar) 220V, 50Hz	96 lbs.	(44kg)

Accessories:


34052	Discharge Valve Kit
34053	Pump Seal Kit



37204 ELECTRIC DIRECT COUPLED TRIPLEX PLUNGER PUMP

Features: On 2-wheeled cart with full perimeter cage, 3.5 gpm/3000 psi (13.25 lpm/200 bar), 7.5 hp., 208/230V, 3-phase, 60Hz motor

Shipping weight.....225 lbs. (102.5kg)



PNEUMATIC HYDROSTATIC TEST PUMP

32150 PNEUMATIC PUMP

Features: 1 gpm/1500 psi (3.8 lpm/105 bar), 100 psi @ 75 cfm required.
(Not on wheeled cart)

Shipping weight.....34 lbs. (11kg)

32300 Same as 32150 except .5 gpm/3000 psi (1.91 lpm/206 bar)
100 psi @ 75 cfm required.....34 lbs. (11kg)



FIRE HOSE TESTERS

Quickly and safely tests fire hoses.

363020 3 gpm/500 psi, (10 lpm/35 bar), 115V, single-phase, 1 hp. capacitor motor, one (1) 2 1/2" NST swivel female quick fill inlet and two (2) 2 1/2" NST male outlets with individual ball valves. Cage mounted on swivel casters. Inlet and outlet hoses not provided.

Shipping weight.....128 lbs. (58kg)



363040 3 gpm/500 psi, (10 lpm/35 bar), 115V, single-phase, 1 hp. capacitor motor, one (1) 2 1/2" NST swivel female quick fill inlet and four (4) 2 1/2" NST male outlets with individual ball valves. Cage mounted on swivel casters. Inlet and outlet hoses not provided.

Shipping weight.....145 lbs. (66kg)



700536 VACUUM TEST ASSEMBLY

An easy way to check a trash pump for proper suction. Verify proper operation before putting a pump into service. Simply prime pump, place flat face over suction port and start pump

1 lb. (.45kg)