

Hy-Brid Lifts[®]

by Custom Equipment



HB-P1027

Specifications & Features **HB-P1027**

OVERALL

LOW FLOOR LOADING

Extremely lightweight design makes the lift easy to push around and allows for use on delicate or sensitive surfaces.

VIRTUALLY MAINTENANCE FREE

Improved life cycle cost of ownership. Standard AGM Battery.

LOW PLATFORM HEIGHT, FULL SWING GATE

Easy access to platform makes fatigue, neck and knee strain a thing of the past.

RAILINGS

ROBUST RAIL SYSTEM

Unique rail technology provides greater durability and resilience against wear and tear on the job site.

NON-SKID DECK

Large durable deck, non-skid.

SCISSORS

OVERSIZED 1.25" (3.18 cm) PINS

Reduces scissor sway. Powerful and reliable with no greasing required.

BASE

BUILT-IN STEP

Allows for a reduced machine size and makes operation and transport to job sites quick and easy.

TOTAL-LOCK REAR CASTERS

Prevents wheel and caster rotation.

AUTO-LOCK BRAKES ON FRONT TIRES

Prevents machine surfing

NON-MARKING WHEELS

Prevents surface scuffs on job site and finished flooring.

SPECS

| HEIGHTS | US | METRIC | PERFORMANCE | US | METRIC |
|-------------------------|----------|--------|---------------------------|-----------|-----------|
| Platform Working Height | 16 ft | 4.82 m | Platform Capacity (total) | 500 lb | 226.8 kg |
| Platform Height (max.) | 10 ft | 3.0 m | Rated Occupancy | 1 person | 1 Person |
| Platform Height (min.) | 27.8 in | 0.71 m | Weight | 870.5 lb | 395 kg |
| Ground Clearance | 1.57 in | 0.04 m | Lift Speed up/down | 13/12 sec | 13/12 sec |
| Stowed Height | 71.1 in | 1.81 m | | | |
| DIMENSIONS | | | FLOOR LOADING | | |
| Overall Width | 27.55 in | 0.70 m | Min. Wheel Load | 250.3 psi | 1726 kPa |
| Overall Length | 43 in | 1.09 m | Max. Wheel Load | 384.1 psi | 2717 kPa |
| Platform Width | 22 in | 0.56 m | Min. Machine Load | 129.6 PSF | 6.21 kPa |
| Platform Length | 37 in | 0.94 m | Max. Machine Load | 204.1 PSF | 9.77 kPa |

1-262-644-1300

www.hybridlifts.com

This brochure is for illustrative purposes only and based on the latest information available at the time of printing. Hy-Brid Lifts reserves the right to make changes at any time, without notice, to specifications, standard and optional equipment. Hy-Brid Lifts™ is a trademark of Custom Equipment, Inc. ©2014 Custom Equipment, Inc. All rights reserved.

Hy-Brid Lifts®