

PIPE CUTTERS

590 AND 591 MANUAL PIPE CUTTER

| Wheeler # | Service (Std) WT Soil Pipe | XH Soil Pipe | No-Hub® | Tile / Clay | Weight |
|-----------|----------------------------|---------------------|---------------------|----------------------|------------------|
| 590-6 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-6" (38mm-150mm) | 4"-6" (100mm-150mm) | 23 lbs. (10.5kg) |
| 590-8 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-6" (38mm-150mm) | 4"-8" (100mm-200mm) | 25 lbs. (11.5kg) |
| 590-10 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-6" (38mm-150mm) | 4"-10" (100mm-250mm) | 27 lbs. (12.5kg) |
| 590-12 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-6" (38mm-150mm) | 4"-12" (100mm-300mm) | 28 lbs. (12.7kg) |
| 590-15 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-6" (38mm-150mm) | 4"-15" (100mm-375mm) | 29 lbs. (13kg) |
| 591-6 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-6" (38mm-150mm) | 4"-6" (100mm-150mm) | 24 lbs. (11kg) |
| 591-8 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-6" (38mm-150mm) | 4"-8" (100mm-200mm) | 25 lbs. (11.5kg) |

490 AND 491 RATCHET PIPE CUTTER



| Wheeler # | Service (Std) WT Soil Pipe | XH Soil Pipe | No-Hub® | Tile / Clay | Weight |
|-----------|----------------------------|---------------------|---------------------|----------------------|------------------|
| 490-6 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-6" (38mm-150mm) | 4"-6" (100mm-150mm) | 18 lbs. (8.5kg) |
| 490-8 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-8" (38mm-200mm) | 4"-8" (100mm-200mm) | 19 lbs. (8.6kg) |
| 490-10 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-8" (38mm-200mm) | 4"-10" (100mm-250mm) | 20 lbs. (9.5kg) |
| 490-12 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-8" (38mm-200mm) | 4"-12" (100mm-300mm) | 22 lbs. (10kg) |
| 490-15 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-8" (38mm-200mm) | 4"-15" (100mm-375mm) | 23 lbs. (10.5kg) |
| 491-6 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-6" (38mm-150mm) | 4"-6" (100mm-150mm) | 18 lbs. (8.5kg) |
| 491-8 | 1½"-6" (38mm-150mm) | 1½"-5" (38mm-125mm) | 1½"-8" (38mm-200mm) | 4"-8" (100mm-200mm) | 19 lbs. (9kg) |

6519 ½" Square Male/Female Drive Ratchet 2 lbs. (.9kg)
 700669 Replacement Drive Screw Assembly

3990 XH RATCHET PIPE CUTTER

| Wheeler # | Service (Std) WT Soil Pipe | XH Soil Pipe | Tile / Clay | Cast Iron Water Class 22 | Weight |
|-----------|----------------------------|--------------------|---------------------|--------------------------|-----------------|
| 3990-6 | 2"-6" (50mm-150mm) | 2"-6" (50mm-150mm) | 2"-6" (50mm-150mm) | 2"-6" (50mm-150mm) | 19 lbs. (9kg) |
| 3990-8 | 2"-8" (50mm-200mm) | 2"-8" (50mm-200mm) | 4"-8" (100mm-200mm) | 2"-6" (50mm-150mm) | 20 lbs. (9.5kg) |

6520 ½" Square Female Drive Ratchet – U.S.A. Made 2 lbs. (.9kg)
 700919 Replacement Drive Screw Assembly

SOIL PIPE COUPLING TORQUE WRENCH

This durable "T-Handle" type torque tool with a contoured comfort-fit handle features a removable socket and a unique locking collar, which allows the tool to be used as an untorqued snug-up or back-off, as well as a conventional torque tool. With the locking collar retracted, the tool torques to the right (tightening), while ratcheting to the left. When proper torque value has been achieved, the mechanism slips internally and over-tightening is impossible.

1977 T-Torque for tightening 5/16" coupling nuts to 60 in. lbs. Weight 1 lb. (.5kg)
 1980 T-Torque for tightening 5/16" coupling nuts to 80 in. lbs. Weight 1 lb. (.5kg)
 1981 T-Torque for tightening 3/8" coupling nuts to 80 in. lbs. Weight 1 lb. (.5kg)
 1982 T-Torque for tightening 5/16" & 3/8" coupling nuts to 80 in. lbs. Weight 1 lb. (.5kg)

275410 5/16" Replacement Socket
 275818 3/8" Replacement Socket

More Torque Wrenches available... see page 56.



Close-up view of "captured screw"



Replaceable Socket



See these pipe cutters in
action on our website at
www.wheelerrex.com

WHEELER-REX HYDRAULIC CUTTERS

Wheeler-Rex Hydraulic Cutters are the solution to cutting larger diameter Cast Iron, Tile and Concrete Pipe. Like the hand operated "snap" cutters, hydraulic cutters are not rotated around pipe. Their remotely operated hydraulic pumps provide the required power. A 2"-3" minimum clearance is all that is needed to wrap cutter chain around pipe. They come complete with pump, hose and case.

INVENTED
BY: WHEELER
REX



2990 HYDRAULIC PIPE CUTTER

| Wheeler # | Service (Std) WT Soil Pipe | XH Soil Pipe | Tile / Clay | Cast Iron Water Class 22 | Cast Iron Water Class 26 | Weight |
|-----------|----------------------------|--------------------|---------------------|--------------------------|--------------------------|-----------------|
| 2990-6 | 2"-6" (50mm-150mm) | 2"-6" (50mm-150mm) | 2"-6" (50mm-150mm) | 2"-6" (50mm-150mm) | NA | 85 lbs. (.39kg) |
| 2990-8 | 2"-8" (50mm-200mm) | 2"-8" (50mm-200mm) | 2"-8" (50mm-200mm) | 2"-6" (50mm-150mm) | NA | 87 lbs. (.40kg) |
| 2990-10 | 2"-10" (50mm-250mm) | 2"-8" (50mm-200mm) | 2"-10" (50mm-250mm) | 2"-6" (50mm-150mm) | NA | 89 lbs. (.41kg) |
| 2990-12 | 2"-10" (50mm-250mm) | 2"-8" (50mm-200mm) | 2"-12" (50mm-300mm) | 2"-6" (50mm-150mm) | NA | 92 lbs. (.42kg) |
| 2990-15 | 2"-10" (50mm-250mm) | 2"-8" (50mm-200mm) | 2"-15" (50mm-375mm) | 2"-6" (50mm-150mm) | NA | 94 lbs. (.43kg) |

INVENTED
BY: WHEELER
REX



3890 HYDRAULIC PIPE CUTTER

| Wheeler # | Service (Std) WT Soil Pipe | XH Soil Pipe | Tile and Concrete | Cast Iron Water Class 22 | Cast Iron Water Class 26 | Weight |
|-----------|----------------------------|----------------------|----------------------|--------------------------|--------------------------|------------------|
| 3890-12 | 4"-12" (100mm-300mm) | 4"-12" (100mm-300mm) | 4"-12" (100mm-300mm) | 4"-12" (100mm-300mm) | 4"-10" (100mm-250mm) | 157 lbs. (.72kg) |
| 3890-15 | 4"-15" (100mm-375mm) | 4"-15" (100mm-375mm) | 4"-15" (100mm-375mm) | 4"-12" (100mm-300mm) | 4"-10" (100mm-250mm) | 163 lbs. (.74kg) |
| 3890-18 | 4"-18" (100mm-450mm) | 4"-18" (100mm-450mm) | 4"-18" (100mm-450mm) | 4"-12" (100mm-300mm) | 4"-10" (100mm-250mm) | 170 lbs. (.77kg) |
| 3890-24 | 4"-18" (100mm-450mm) | 4"-18" (100mm-450mm) | 4"-24" (100mm-600mm) | 4"-12" (100mm-300mm) | 4"-10" (100mm-250mm) | 178 lbs. (.88kg) |

INVENTED
BY: WHEELER
REX



5590 HYDRAULIC PIPE CUTTER

| Wheeler # | Service (Std) WT Soil Pipe | XH Soil Pipe | Tile and Concrete | Cast Iron Water Class 22 | Cast Iron Water Class 26 | Weight |
|-----------|----------------------------|----------------------|----------------------|--------------------------|--------------------------|------------------|
| 5590-18 | 6"-18" (150mm-450mm) | 6"-18" (150mm-450mm) | 6"-18" (150mm-450mm) | 6"-18" (150mm-450mm) | 6"-18" (150mm-450mm) | 200 lbs. (.91kg) |
| 5590-20 | 6"-18" (150mm-450mm) | 6"-18" (150mm-450mm) | 6"-20" (150mm-500mm) | 6"-20" (150mm-500mm) | 6"-18" (150mm-450mm) | 213 lbs. (.97kg) |
| 5590-24 | 6"-18" (150mm-450mm) | 6"-18" (150mm-450mm) | 6"-24" (150mm-600mm) | 6"-20" (150mm-500mm) | 6"-18" (150mm-450mm) | 230 lbs. (105kg) |
| 5590-36 | 6"-18" (150mm-450mm) | 6"-18" (150mm-450mm) | 6"-36" (150mm-900mm) | 6"-20" (150mm-500mm) | 6"-18" (150mm-450mm) | 269 lbs. (122kg) |

HYDRAULIC PUMP FLUID

(Wheeler Hydraulic Cutter guarantees valid only when Hydroyl fluid is used.)

| | | |
|------|-------------|---------------|
| 3801 | 1 Qt. | 2 lbs. (.9kg) |
| 3804 | 1 Gal. | 8 lbs. (4kg) |

Gallons are available in cases of six.



PIPE CUTTER CHAINS



490 RATCHET, 590 MANUAL & 1790 JR. HYDRAULIC

| Part No. | | Length | No. of pins | Weight |
|----------|--|---------|-------------|-----------------|
| 522 | Chain for 6" Pipe | 26 1/4" | 21 | 5 lbs. (2.3kg) |
| 532 | Chain for 6" Pipe with rollers for No-Hub® | 26 1/4" | 21 | 5 lbs. (2.3kg) |
| 528 | Chain for 8" Pipe | 36" | 29 | 7 lbs. (3kg) |
| 533 | Chain for 8" Pipe with rollers for No-Hub® | 36" | 29 | 8 lbs. (3.6kg) |
| 5210 | Chain for 10" Pipe | 43 3/4" | 35 | 8 lbs. (3.6kg) |
| 5212 | Chain for 12" Pipe | 51" | 41 | 10 lbs. (4.5kg) |
| 5215 | Chain for 15" Pipe | 58 1/2" | 47 | 11 lbs. (5kg) |

FOR CONVERTING YOUR PRESENT CHAIN TO CUT LARGER SIZES

| | | | | |
|-------|---|---------|----|----------------|
| 5256 | 6" to 8", 8" to 10", 10" to 12", 12" to 15" | 10" | 8 | 2 lbs. (.9kg) |
| 5258 | 6" to 10", 8" to 12", 10" to 15" | 17 1/2" | 14 | 4 lbs. (1.8kg) |
| 52510 | 6" to 12", 8" to 15" | 25" | 20 | 5 lbs. (2.3kg) |
| 52512 | 6" to 15" | 32 1/2" | 26 | 6 lbs. (2.7kg) |
| 519 | Kit to convert 590 Cutter to 591 No-Hub® Cutter or 490 Cutter to 491 No-Hub® Cutter | | | |

3990 RATCHET PIPE CUTTER

| Part No. | | Length | No. of Pins | Weight |
|----------|-------------------|--------|-------------|------------------|
| 700987 | Chain for 6" Pipe | 26" | 21 | 7 lbs. (3kg) |
| 701077 | Chain for 8" Pipe | 36" | 29 | 8.5 lbs. (3.8kg) |

2990 HYDRAULIC CUTTER

| Part No. | | Length | No. of pins | Weight |
|----------|--------------------------------------|---------|-------------|--------------------|
| 1926 | Chain for 6" Pipe | 26 1/4" | 21 | 7 lbs. (3kg) |
| 1924 | Chain for 8" Pipe (replaces 2924) | 36 1/4" | 29 | 8 1/2 lbs. (3.8kg) |
| 192410 | Chain for 10" Pipe (replaces 292410) | 46 1/4" | 37 | 11 lbs. (5kg) |
| 192412 | Chain for 12" Pipe (replaces 292412) | 53 1/4" | 43 | 13 lbs. (5.9kg) |
| 192415 | Chain for 15" Pipe (replaces 292415) | 61 1/4" | 49 | 15 lbs. (6.8kg) |

FOR CONVERTING YOUR PRESENT CHAIN TO CUT LARGER SIZES

(Note – Old and new style chain extensions NOT interchangeable)

| | | | | |
|-------|-------------------------------|---------|----|-------------------|
| 19010 | 8" Cutter to 10" | 10" | 8 | 2 1/2 lbs. (1kg) |
| 19012 | 8" Cutter to 12" | 17 1/2" | 14 | 4 1/2 lbs. (2kg) |
| 19015 | 8" Cutter to 15" | 25" | 20 | 6 1/2 lbs (2.9kg) |
| 2905 | Adjusting link for 2990 Chain | | | |

3890 HEAVY DUTY HYDRAULIC CUTTER

| Part No. | | Length | No. of pins | Weight |
|----------|--------------------|---------|-------------|------------------|
| 3824 | Chain for 12" Pipe | 50 3/4" | 29 | 24 lbs. (10.9kg) |
| 382415 | Chain for 15" Pipe | 63" | 37 | 31 lbs. (14kg) |
| 382418 | Chain for 18" Pipe | 76 1/2" | 43 | 35 lbs. (15.9kg) |
| 382424 | Chain for 24" Pipe | 97 1/2" | 55 | 46 lbs. (20.9kg) |

FOR CONVERTING YOUR PRESENT CHAIN TO CUT LARGER SIZES

| | | | | |
|--------|-------------------|---------|----|----------------|
| 382515 | 12" Cutter to 15" | 14" | 8 | 7 lbs. (3kg) |
| 382518 | 12" Cutter to 18" | 24 1/2" | 14 | 11 lbs. (5kg) |
| 382520 | 12" Cutter to 20" | 35" | 20 | 11 lbs. (5kg) |
| 382524 | 12" Cutter to 24" | 46 1/2" | 26 | 22 lbs. (10kg) |

5590 SUPER HYDRAULIC CUTTER

| Part No. | | Length | No. of pins | Weight |
|----------|--------------------|---------|-------------|-------------------|
| 5524 | Chain for 18" Pipe | 72 1/2" | 29 | 70 lbs. (31.8kg) |
| 552420 | Chain for 20" Pipe | 82 1/2" | 33 | 80 lbs. (36.4kg) |
| 552424 | Chain for 24" Pipe | 97" | 39 | 95 lbs. (43.2kg) |
| 552436 | Chain for 36" Pipe | 142" | 57 | 134 lbs. (60.9kg) |

FOR CONVERTING YOUR PRESENT CHAIN TO CUT LARGER SIZES

| | | | | |
|--------|-------------------|-----|----|------------------|
| 552520 | 18" Cutter to 20" | 10" | 4 | 10 lbs. (4.5kg) |
| 552524 | 18" Cutter to 24" | 25" | 10 | 25 lbs. (11.4kg) |
| 552536 | 18" Cutter to 36" | 70" | 28 | 64 lbs. (29.1kg) |

NOTE: Hydraulic cutter chain parts: individual pins, links and wheels are only available with factory installation. Hydraulic cutter chain extensions are available only through authorized service stations unless installed by the factory.

PIPE CUTTERS

CONTINUED



INTERNAL CAST IRON PIPE CUTTER (CAPITOL STYLE CUTTER)

Cuts Cast Iron from the inside out!!

Designed to eliminate the difficulty plumbers have in setting toilet bowls, urinals and similar fixtures due to the shortness of the closet horn. Make cuts where nothing else can!

| | | |
|-------|-------------------|---------------|
| 32900 | 3" Cast Iron..... | 14 lbs. (6kg) |
| 42900 | 4" Cast Iron..... | 16 lbs. (7kg) |

Replacement Cutter Wheels:

| | |
|--------|-------------------------------------|
| 700201 | Cutter Wheel for CI for 32900/42900 |
|--------|-------------------------------------|

STEEL PIPE CUTTERS

Two models designed for fast, easy cutting of steel pipes. Both models come with an extra long shank which protects adjustment threads and an extra large handle for quick, easy adjustment.

| | | |
|------|----------------------------------|-------------------|
| 2690 | For 1/8"-2" steel pipe | 5.6 lbs. (2.5kg) |
| 8081 | Cutter Wheel for steel | |
| 8082 | Cutter Wheel for stainless steel | |
| 4690 | For 2"-4" steel pipe..... | 17.5 lbs. (7.9kg) |
| 8016 | Cutter Wheel for steel | |
| 8004 | Cutter Wheel for stainless steel | |

HINGED PIPE CUTTER

Four-wheel cutter, featuring a unique guide bar design that ensures both smooth operation and accurate precise pipe cutting. Needs only 90° to 110° handle swing, and only 4 inch clearance. Universal cutter wheels are ideal for cutting most metals and are interchangeable with many other makes of hinged pipe cutters.

| | | |
|-------|-------------------------------|----------------|
| 5090 | 1/2"-2" pipe capacity..... | 6 lbs. (3kg) |
| 95041 | 2 1/2"-4" pipe capacity | 14 lbs. (6kg) |
| 95061 | 4"-6" pipe capacity..... | 22 lbs. (10kg) |
| 95081 | 6"-8" pipe capacity | 28 lbs. (13kg) |
| 95121 | 8"-12" pipe capacity..... | 39 lbs. (18kg) |

Replacement Cutter Wheels:

| | |
|------|---|
| 8039 | for 5090 for steel |
| 8050 | for 95041 for steel |
| 8052 | for 95061 for steel |
| 8054 | for 95081, 95121 for steel |
| 8051 | for 95041 for CI/DI |
| 8053 | for 95061, 95081, 95121 for CI/DI |
| 8076 | for 95061, 95081, 95121 / universal wheel |

PIPE CLEANER (Descaler)

A versatile scraper for removing mud and scale from pipe surfaces. Makes for faster cutting and better repairs and joints. Belt material is light, strong and non-corroding. Angled blades promote self-cleaning. Belt is replaceable, longer length reduces back strain.

| | | |
|------|-----------------------------------|----------------|
| 1300 | For 3-12" diameter, 45" OAL..... | 4 lbs. (2kg) |
| 1301 | Replacement Belt, 45" | 3 lbs. (1.5kg) |
| 1350 | For 12-36" diameter, 72" OAL..... | 5 lbs. (2.5kg) |
| 1351 | Replacement Belt, 72" | 4 lbs. (2kg) |



PIPE CUTTERS

CONTINUED



See this pipe cutter in action on our website at www.wheelerrex.com



Tripod Pipe Support sold separately

2500 KWIKSNAP

A semi-auto production cutter for cast iron soil pipe from the company who invented the "squeeze and pop" principle. Cuts 1½"-6" soil pipe fast, easy and safely. Much cleaner than chop saws. Electric/hydraulic power is quiet and reliable. Built in handle and pneumatic tires for easy transport.

Gross weight, packed375 lbs. (171kg)
Net weight258 lbs. (118kg)

Features:

- Five second cutting cycle time
- Unique chain design eliminates resetting for each cut on same size
- Semi-auto operation
- Much cleaner than sawing
- Dual pressure switches for safety

Specifications:

- Dimensions 32" x 20" x 50"
- 10" pneumatic wheels
- 1 hp. electric motor, 11.2 amps, 115V, 60Hz

5222 Replacement Cutter Chain5 lbs. (2.3kg)



In two minutes of cutting time:

Compare!!




Chop Saw



Conventional Cutter



KwikSnap 2500



2525 KWIKSNAP TABLE

A modular table design that quickly attaches to the 2500 KwikSnap. Simply drill holes in the KwikSnap cabinet to attach. Even with the tables attached, you will still have full access to all maintenance doors. Additional table section assemblies and leg/coupling assemblies can easily be added to either side of the KwikSnap.

2525 KwikSnap Table250 lbs. (114kg)

Assembly consists of three (3) 3' long table sections with removable rollers (a total of 9 linear feet), two (2) table leg assemblies, two (2) coupling brackets, two (2) machine to table brackets, four (4) table-leg coupling brackets, two (2) flipper assemblies and one (1) fence assembly. The fence assembly is easy to install and adjust with two quick action levers that fit into T-slots in the table top. Dimensions are 3' long x 16" wide x 30" tall when fitted to the leg assembly. Table legs have holes to anchor legs to floor as well as leveling bolts with jam nuts to eliminate the need for any shimming to level table.

The KwikSnap doors and top can be opened without removing the KwikSnap Table.



2526 Table Section Assembly55 lbs. (25kg)

The table assembly consists of one (1) 3' long x 16" wide x 4" tall table section complete with roller coupling brackets and fasteners, ready to attach to your existing 2525 table. (No leg or leg couplings are included.)

2527 Leg and Coupling Assembly37 lbs. (17kg)

Consists of leg with leg couplings.



Flipper Assembly



Table Top with Fence



Leg Adjustment

PIPE CUTTERS

CONTINUED

Free
CD
Available



See these pipe cutters in
action on our website at
www.wheelerrex.com



Blade cover removed for
photographic purposes.

THE PIPEMASTER

General Information:

Unit consists of a cutting head with internal gears which operate the drive wheels and blade shaft. Cutting blades (except for No. 4616) must be cooled with water during cutting and are fully enclosed for safety. The cutter is held onto the pipe by a wide roller chain which is tensioned with a threaded take-up mechanism. A chart is included which tells the operator how much chain is required for various sizes of pipe. PipeMaster comes standard with cutting head, roller chain, wedges and water supply tank in a wood case. Blades are chosen based on pipe material and are not included with the basic machine. Maximum wall thickness for cutting is 1". The unit has a hydraulic motor which requires an external hydraulic power source. See our Model 6500 Power Pak and 701185 Bypass Valve on the next page.

| | | | |
|------|-----------------------------------|--------------------------|--------|
| 4624 | PipeMaster 6" to 24" (150–600mm) | Shipping weight 99 lbs. | (45kg) |
| 4648 | PipeMaster 6" to 48" (150–1200mm) | Shipping weight 112 lbs. | (51kg) |

PipeMaster Features:

- Maximum hydraulic requirements 6 gpm/1500 psi
- Gearbox: Worm Drive with 80–90W gear oil required
- Cutting speed: 3" (150mm) of surface travel per minute
1" (25mm) of diameter per minute
- Cutting Clearance: Radial 8" (200mm); Axial 16" (400mm)
- Blade Speed: 1200 RPM
- Construction: Aluminum gearbox, side plated steel; bronze gears, steel roller chain, drive wheels are aluminum with urethane covering


Cutting 30" pipe and larger may require special instructions to complete the cut.

PIPEMASTER BLADES

Three blades for Cast Iron, Ductile Iron and Steel Pipes. Available with diamond or carbide tipped. These blades will fit the Wheeler-Rex PipeMaster as well as Universal and Utility Cutters from Reed Manufacturing, Keel and WACHS.



Blade No. 4706
6" Carbide-tipped
Blade for Steel Pipe



Blade No. 4606
6" Diamond Blade for
CI/DI Pipe



Blade No. 4616
6" Economy Diamond
Blade for DI Pipe

| | |
|------|--|
| 4706 | 6" Carbide Tipped Blade for steel pipes |
| 4606 | 6" Diamond Blade for cast iron, ductile iron and clay pipes |
| 4616 | 6" Economy Diamond Blade for ductile iron pipes. Cut dry or wet. Low price and excellent performance make this blade the best value on the market!!! |



PipeMaster comes with these as standard accessories.

PIPEMASTER ACCESSORIES

- 700970 Drive Wheels for 6" pipe (2 required)
- 276693 Water Supply Tank, 4 gallon
- 700821 20' Hydraulic Hose Assembly complete with male/female FF quick disconnects
- 276288 Flat Face Male Quick Disconnect
- 276289 Flat Face Female Quick Disconnect
- 4686 Roller Chain, one link section
- 4685 Steel Wedge, set of 6 wedges
- 4606 6" Diameter Diamond Blade for CI, DI & clay
- 4706 6" Tungsten Carbide Tipped Blade for steel
- 4616 6" Economy Diamond Blade for DI pipe

Different drive wheels are required to cut 6" pipes (see part number 700970 above).

Number of Chain Links Required:

| Pipe Diameter | 24" (600mm) | 48" (1200mm) |
|-----------------|-------------|--------------|
| Number of Links | 34 pieces | 62 pieces |



6500 HYDRAULIC POWER PAK 232 lbs. (105kg)

Features:

- Maximum hydraulic information: 6 gpm/1500 psi
- Adjustable pressure-relief valve
- Complete with 6.5 hp. Honda engine, on two-wheeled cart with pneumatic tires and cage
- Comes with two 700821 – 20' Hydraulic Hose Assemblies complete with male/female FF quick disconnects
- Can be used to power other hydraulic tools

701185 BYPASS VALVE KIT

Bypass Valve 6 gpm/1500 psi 10 lbs. (4.6kg)



Bypass Valve Kit is designed to be used with your truck, skid loader, backhoe or tractor's hydraulic system for use with the Wheeler Rex PipeMaster. The 701185 will adapt your current hydraulic system to the specs required to operate the PipeMaster (maximum 6 gpm/1500 psi). Weight is only 10 pounds and it is easy to connect. The PipeMaster's hydraulic lines will directly attach to the quick disconnects for both input and output points on the Bypass Valve. Hydraulic lines are required and are not included with the 701185 and are available as an additional accessory.*

*700821 20' Hydraulic Hose Assembly complete with male/female FF quick disconnects

Features:

- Maximum input from alternative hydraulic power source: 0–30 gpm/0–3000psi
- Maximum output from Bypass valve: 0–6 gpm/0–1500psi