

PORTABLE & STATIONARY AIR COMPRESSORS



Single Stage Gasoline

Do-it-yourself jobs can seem daunting. Mi-T-M's hand carry single stage 5-gallon air compressors make your jobs easier and more efficient by supplying the extra power you need. Our gasoline models are perfect for remote jobsites.

5-Gallon

Limited Warranties:

1 Year Compressor Pump **3 Year** Honda Engine

1 Year Mi-T-M Engine **5 Year** Subaru Engine



AM1-HH04-05M

Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Canister inlet air filter

Frame

- ✓ Powder coated steel frame and roll cage design
- ✓ 5-gallon powder coated tank assembly
- ✓ Protective pump/motor housing

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Drain valves and pressure relief valves
- ✓ Start/stop control set at 95 to 125-PSI

MODEL NUMBER	CFM @ PSI	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-HH04-05M	5.4 @ 90	118cc Honda OHV	Single stage	Cast iron	Oil lubricated aluminum	5-gallon	Pneumatic	21x17.5x22.25in.	85 lb.	77 lb.
AM1-HM04-05M	5.4 @ 90	136cc Mi-T-M OHV	Single stage	Cast iron	Oil lubricated aluminum	5-gallon	Pneumatic	21x17.5x22.25in.	85 lb.	77 lb.
AM1-HS45-05M	5.4 @ 90	126cc Subaru OHC	Single stage	Cast iron	Oil lubricated aluminum	5-gallon	Cable throttle	21x17.5x22.25in.	93 lb.	85 lb.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
70-0357	Engine oil drain	AM1-HH04-05M & AM1-HM04-05M
70-0380	Engine oil drain	AM1-HS45-05M

Single Stage Gasoline

8-Gallon

Designed for jobs that require more power than standard tools can deliver.
This Mi-T-M portable air compressor is ideal for light to moderate use.

Limited Warranties:

2 Year
Pump Exchange
See page 58 for information

3 Year
Kohler Engine

3 Year
Honda Engine

5 Year
Subaru Engine



AM1-PK07-08M

Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Large canister intake filter

Frame

- ✓ Powder coated 8-gallon twin tank receivers
- ✓ 3/16-inch base plate to reduce vibration
- ✓ 16-gauge powder coated two-piece belt guard

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Manual drain valves for proper maintenance
- ✓ 12-inch fly wheel
- ✓ Quality pilot valve unloader

To see more online, scan here
or go to www.mitm.com:



MODEL NUMBER	CFM @ PSI	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PH65-08M	13.9 @ 90	196cc Honda OHV	Single stage	Cast iron	Splash lubricated cast iron	8-gallon	Pneumatic	44.5x18.5x27in.	200 lb.	175 lb.
AM1-PK07-08M	13.9 @ 90	208cc Kohler OHV	Single stage	Cast iron	Splash lubricated cast iron	8-gallon	Cable throttle	44.5x18.5x27in.	200 lb.	175 lb.
AM1-PR07-08M	13.9 @ 90	211cc Subaru OHC	Single stage	Cast iron	Splash lubricated cast iron	8-gallon	Cable throttle	44.5x18.5x27in.	200 lb.	175 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
33-0294	Cable throttle control	AM1-PH65-08M	AW-6000-1002	Equipment cover	All models
70-0357	Engine oil drain	Honda & Kohler models	AX-0003	Manual drain/regulator/metal bowl	All models
70-0380	Engine oil drain	AM1-PR07-08M	AX-0067	Electric start (battery and cables not included)	AM1-PR07-08M

Single Stage Gasoline

This gas driven, portable, single stage 20-gallon air compressor features a rugged handle and large tires that allow for greater portability and high quality performance.

20-Gallon

Limited Warranties:

2 Year
Pump Exchange

See page 58 for information

5 Year
Subaru Engine

3 Year
Honda Engine



AM1-PH65-20M

Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Large canister intake filter

Frame

- ✓ Powder coated ASME coded 20-gallon receiver tank
- ✓ 3/16-inch base plate to reduce vibration
- ✓ 16-gauge powder coated two-piece belt guard

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Manual drain valves for proper maintenance
- ✓ 12-inch fly wheel
- ✓ Quality pilot valve unloader

To see more online, scan here
or go to www.mitm.com:



MODEL NUMBER	CFM @ PSI	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PH65-20M	13.9 @ 90	196cc Honda OHV	Single stage	Cast iron	Splash lubricated cast iron	20-gallon	Pneumatic	37x23.5x33in.	272 lb.	212 lb.
AM1-PR07-20M	13.9 @ 90	211cc Subaru OHC	Single stage	Cast iron	Splash lubricated cast iron	20-gallon	Cable throttle	37x23.5x33in.	272 lb.	212 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
33-0294	Cable throttle control	AM1-PH65-20M	AW-6000-1002	Equipment cover	All models
7-0228A01	Rear lifting handle (N/A for models with electric start option)	All models	AX-0003	Manual drain/regulator/metal bowl	All models
70-0357	Engine oil drain	AM1-PH65-20M	AX-0027	Stationary kit	All models
70-0380	Engine oil drain	AM1-PR07-20M	AX-0067	Electric start (battery and cables not included)	AM1-PR07-20M

Two Stage Gasoline

8-Gallon

Ideal for both contractors and remodelers, this two stage air compressor provides a reliable air source on remote jobsites.

Limited Warranties:

2 Year
Pump Exchange
See page 58 for information

3 Year
Kohler Engine

3 Year
Honda Engine

5 Year
Subaru Engine



AM2-PR09-08M

Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Large canister intake filter

Frame

- ✓ Powder coated 8-gallon twin tank receivers
- ✓ $\frac{3}{16}$ -inch base plate to reduce vibration
- ✓ 14-gauge powder coated two-piece belt guard

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Manual drain valves for proper maintenance
- ✓ 16.5-inch fly wheel
- ✓ Quality pilot valve unloader

To see more online, scan here
or go to www.mitm.com:



MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-08M	17.2 @ 175	270cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	8-gallon	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PK95-08M	17.2 @ 175	277cc Kohler OHV	Two stage	Cast iron	Splash lubricated cast iron	8-gallon	Cable throttle	44x26x31in.	330 lb.	260 lb.
AM2-PR09-08M	17.2 @ 175	265cc Subaru OHC	Two stage	Cast iron	Splash lubricated cast iron	8-gallon	Pneumatic	44x26x31in.	330 lb.	260 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
33-0294	Cable throttle control	AM2-PH09-08M	AX-0003	Manual drain/regulator/metal bowl	All models
33-0401	Cable throttle control	AM2-PR09-08M	AX-0015	Electric start (battery and cables not included)	AM2-PH09-08M
AW-6000-1002	Equipment cover	All models	AX-0041	Electric start (battery and cables not included)	AM2-PR09-08M

Two Stage Gasoline

Strong and durable, this unit can store ample pressure and is available in both portable or stationary.

20-Gallon

Limited Warranties:

2 Year
Pump Exchange

See page 58 for information

3 Year
Honda Engine



AM2-SH09-20M shown with
AX-0015 (electric start option)

Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Large canister intake filter

Frame

- ✓ Powder coated ASME coded 20-gallon receiver tank
- ✓ 3/16-inch base plate to reduce vibration
- ✓ 14-gauge powder coated two-piece belt guard

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Manual drain valves for proper maintenance
- ✓ 16.5-inch fly wheel
- ✓ Quality pilot valve unloader

To see more online, scan here
or go to www.mitm.com:



PORTABLE MODEL

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-20M	17.2 @ 175	270cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	20-gallon	Pneumatic	46x26x39.5in.	356 lb.	306 lb.

STATIONARY MODEL

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-SH09-20M	17.2 @ 175	270cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	20-gallon	Pneumatic	37x18x38in.	356 lb.	306 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
33-0294	Cable throttle control	All models	AX-0003	Manual drain/regulator/metal bowl	All models
AW-0007-0196	Rear lifting handle (N/A for models with electric start option)	AM2-PH09-20M	AX-0015	Electric start (battery and cables not included)	All models
AW-6000-1002	Equipment cover	All models	AX-0017	Electric start (battery and cables included)	All models

Two Stage Gasoline

30 & 80-Gallon & Base-Mount

Two stage air compressors provide a reliable air source for commercial, industrial and automotive applications.

Limited Warranties:

2 Year
Pump Exchange

See page 58 for information

3 Year
Kohler Engine



UM
30-Gallon
Models



U
80-Gallon
Models

3 Year
Honda Engine

5 Year
Subaru Engine

Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Oil level sight indicator

Engine

- ✓ Electric start standard (battery and cables not included)

Frame

- ✓ Powder coated ASME coded 30 or 80-gallon receiver tank (Tank-mounted models only)
- ✓ 3/16-inch base plate to reduce vibration
- ✓ 14-gauge powder coated two-piece belt guard
- ✓ Tabbed design offers flexible installation

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ ASME safety valves
- ✓ 16.5-inch fly wheel
- ✓ Tank drain valve



ABS-14S-30H

To see more online, scan here
or go to www.mitm.com:



TANK-MOUNTED MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-13H-30H	29.0 @ 175	389cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	30-gallon	Pneumatic	42x19x45in.	480 lb.	416 lb.
ABS-14K-30H	29.0 @ 175	429cc Kohler OHV	Two stage	Cast iron	Splash lubricated cast iron	30-gallon	Cable throttle	42x19x45in.	480 lb.	416 lb.
ABS-14S-30H	29.0 @ 175	404cc Subaru OHC	Two stage	Cast iron	Splash lubricated cast iron	30-gallon	Cable throttle	42x19x45in.	480 lb.	416 lb.
ABS-13H-80H	29.0 @ 175	389cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	Pneumatic	52x26.5x53in.	560 lb.	496 lb.
ABS-14S-80H	29.0 @ 175	404cc Subaru OHC	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	Cable throttle	52x26.5x53in.	560 lb.	496 lb.

BASE-MOUNTED MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-13H-B	29.0 @ 175	389cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	Base-mount	Pneumatic	36.5x19x28in.	279 lb.	215 lb.
ABS-14S-B	29.0 @ 175	404cc Subaru OHC	Two stage	Cast iron	Splash lubricated cast iron	Base-mount	Cable throttle	36.5x19x28in.	279 lb.	215 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
3-0304	Pump	All models	AW-6000-1002	Equipment cover	All models
33-0548	Cable throttle control	Honda models	IX-0001	Vibration pads	Tank-mounted models
854-0093	Service truck mount kit (recommended for models that are mounted in service truck applications)	All models			

Single Stage Electric

Work Pro® Series

The Work Pro® line of equipment is designed for both the serious do-it-yourselfer and professional who requires a high level of performance from their equipment. The Work Pro® Series of electric air compressors offer both ease of use and everything you need to get the job done right.

3, 4 & 5-Gallon

Limited Warranties:

1 Year
Compressor Pump



1 Year
Electric Motor



NEMA 5-15P,
15-amp plug



AM1-PE02-05M



AM1-HE15-03M

Compressor Pump

- ✓ Copper line discharge hose
- ✓ Cartridge air filter

Motor

- ✓ Thermal motor overload protection

Frame

- ✓ Powder coated tank assembly
- ✓ Protective pump/motor housing

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Drain valves and pressure relief valves
- ✓ Quick connect fittings
- ✓ Start/stop control set at 95 to 125-PSI

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	TYPE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-HE15-03M	3.0 @ 90	1.5 HP, 120V, 15.0A	Single stage	Cast iron	Oil lubricated aluminum	3-gallon	Hand carry	NEMA 5-15P	22.5x10.5x22.25in.	46 lb.	41 lb.
AM1-HE02-04M	4.2 @ 90	2.0 HP, 120V, 15.0A	Single stage	Cast iron	Oil lubricated aluminum	4-gallon	Hand carry	NEMA 5-15P	21.5x16x15.75in.	68 lb.	60 lb.
AM1-PE02-05M	4.2 @ 90	2.0 HP, 120V, 15.0A	Single stage	Cast iron	Oil lubricated aluminum	5-gallon	Portable	NEMA 5-15P	19.75x19x33.5in.	79 lb.	69 lb.

Single Stage Electric

5-Gallon

Limited Warranties:

1 Year
Compressor Pump



1 Year
Electric Motor



NEMA 5-15P,
15-amp plug

This electric air compressor makes your jobs easier and more efficient by supplying extra air power. Simply plug it into the nearest outlet and go.



AC1-HE02-05M1

Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Canister inlet air filter

Motor

- ✓ Thermal motor overload protection

Frame

- ✓ Powder coated tank assembly
- ✓ Protective pump/motor housing

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Drain valves and pressure relief valves
- ✓ Quick connect fittings
- ✓ Start/stop control set at 95 to 125-PSI

To see more online, scan here
or go to www.mitm.com:



MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AC1-HE02-05M1	4.3 @ 90	2.0 HP, 120V, 14.0A	Single stage	Cast iron	Oil lubricated aluminum	5-gallon	NEMA 5-15P	20.5x15.5x17.5in.	70 lb.	61 lb.

Single Stage Electric

This air compressor offers maximum efficiency and flexibility. The industrial electric motor features an auto start/stop and a 10-inch fly wheel for extra cooling and longer life.

8-Gallon

Limited Warranties:

1 Year
Electric Motor



2 Year
Pump Exchange

CSA
CERTIFIED

See page 58 for information



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Large canister intake filter

Motor

- ✓ Auto start/stop (continuous run optional)
- ✓ Thermal overload motor protection

Frame

- ✓ Powder coated 8-gallon twin tank receivers
- ✓ 3/16-inch base plate to reduce vibration
- ✓ 16-gauge powder coated two-piece belt guard

AM1-PE15-08M

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Manual drain valves for proper maintenance
- ✓ 10-inch fly wheel
- ✓ Industrial-grade pressure switch

To see more online, scan here
or go to www.mitm.com:



MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PE15-08M	7.3 @ 90	1.5 HP, 120V, 13.2A	Single stage	Cast iron	Splash lubricated cast iron	8-gallon	NEMA 5-15P	44.5x18.5x25in.	190 lb.	170 lb.
AM1-PE02-08M	9.2 @ 90	2.0 HP, 120V, 18.8A	Single stage	Cast iron	Splash lubricated cast iron	8-gallon	NEMA 5-20P	44.5x18.5x25in.	190 lb.	170 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover	All models	AX-0003	Manual drain/regulator/metal bowl	All models
AX-0002	Auto drain/regulator/plastic bowl	All models	AX-0005	Dual control	All models

Single Stage Electric

20-Gallon

Packed with features that let you take on demanding jobs this electric model has more storing capacity and is the perfect solution for service shops.

Limited Warranties:

1 Year
Electric Motor



2 Year
Pump Exchange

See page 58 for information



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



UM



Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Large canister intake filter

Motor

- ✓ Auto start/stop (continuous run optional)
- ✓ Thermal overload motor protection

Frame

- ✓ Powder coated ASME coded 20-gallon receiver tank
- ✓ 3/16-inch base plate to reduce vibration
- ✓ 16-gauge powder coated two-piece belt guard

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Manual drain valves for proper maintenance
- ✓ 10-inch fly wheel
- ✓ Industrial-grade pressure switch

AM1-PE02-20M

To see more online, scan here
or go to www.mitm.com:



MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PE15-20M	7.3 @ 90	1.5 HP, 120V, 13.2A	Single stage	Cast iron	Splash lubricated cast iron	20-gallon	NEMA 5-15P	40x24x32in.	265 lb.	196 lb.
AM1-PE02-20M	9.2 @ 90	2.0 HP, 120V, 18.8A	Single stage	Cast iron	Splash lubricated cast iron	20-gallon	NEMA 5-20P	40x24x32in.	260 lb.	198 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover	All models	AX-0003	Manual drain/regulator/metal bowl	All models
AX-0002	Auto drain/regulator/plastic bowl	All models	AX-0008	Dual control	All models

Two Stage Electric

80 & 120-Gallon

These 80 and 120-gallon horizontal and vertical models have a large capacity air storage offering longer run times and faster recovery.



Limited Warranties:

1 Year
Electric Motor

2 Year
Pump Exchange

See page 58 for information



CSA
CERTIFIED
AAS Models
Only

U

Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Oil level sight indicator

Frame

- ✓ Powder coated ASME coded 80 or 120-gallon receiver tank
- ✓ $\frac{3}{16}$ -inch base plate to reduce vibration
- ✓ 14-gauge powder coated two-piece belt guard

Components

- ✓ ASME safety valves
- ✓ Large fly wheel
- ✓ Intake filter/silencer
- ✓ Tank shut-off valve



ACS-23175-80V

To see more online, scan here
or go to www.mitm.com:



HORIZONTAL MODELS

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	DIMENSIONS (LxWxH)	BOLT DOWN (LxW)	SHIP WT.	NET WT.
AAS-23105-80H	17.8 @ 175	5.0 HP, 230V, 1Ø, 23.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	52x26.5x53in.	20.75x23.5in.	570 lb.	499 lb.
ACS-23175-80H	23.5 @ 175	7.5 HP, 230V, 1Ø, 31.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	52x26.5x53in.	20.75x23.5in.	665 lb.	594 lb.
ADS-23310-120H	34.2 @ 175	10.0 HP, 230V, 3Ø, 26.8A	Two stage	Cast iron	Splash lubricated cast iron	120-gallon	74x26.5x58in.	34.5x23.5in.	904 lb.	785 lb.
AES-23315-120H	46.5 @ 175	15.0 HP, 230V, 3Ø, 38.0A	Two stage	Cast iron	Splash lubricated cast iron	120-gallon	74x26.5x58in.	34.5x23.5in.	995 lb.	876 lb.

VERTICAL MODELS

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	DIMENSIONS (LxWxH)	BOLT DOWN (LxW)	SHIP WT.	NET WT.
AAS-23105-80V	17.8 @ 175	5.0 HP, 230V, 1Ø, 23.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	33x25x73in.	15.63x15.63in.	570 lb.	499 lb.
ACS-23175-80V	23.5 @ 175	7.5 HP, 230V, 1Ø, 31.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	33x25x73in.	15.63x15.63in.	665 lb.	594 lb.

Note: Starter is not included with unit, must add starter option.

Consult factory for availability of more air compressor models and voltages.

Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
IX-0013	Starter (5.0 HP)	AAS-23105-80H & AAS-23105-80V	IX-0023	Starter (10.0 HP)	ADS-23310-120H
IX-0017	Starter (7.5 HP)	ACS-23175-80H & ACS-23175-80V	IX-0026	Starter (15.0 HP)	AES-23315-120H

Consult factory for availability of more options and accessories.

M Series

Two Stage Electric

80 & 120-Gallon

The ultimate in air compressors, the M Series comes complete with all available options to meet the most demanding industrial air needs of machine shops, automotive repair facilities and general industrial applications.

These standard features are what sets the M Series air compressors apart from our standard line-up.



NEMA-4 starter box with magnetic motor starter for thermal overload protection



Hour meter displays the number of hours compressor has been in operation



Vibration isolator pads protect the tank from stress




ACS-23105-80VM



Air-cooled aftercooler removes up to 65% of moisture and drops temperature within 10°F of ambient



Low oil sensor does not allow unit to start when oil levels fall below an adequate level



Tank drain automatically drains liquid from air receiver

Two Stage Electric

M Series

80 & 120-Gallon

Limited Warranties:

1 Year
Electric Motor

2 Year
Pump Exchange
See page 58 for information



To see more online, scan here
or go to www.mitm.com:



Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Oil level sight indicator

Frame

- ✓ Powder coated ASME coded 80 or 120-gallon receiver tank
- ✓ 3/16-inch base plate to reduce vibration
- ✓ Totally enclosed heavy-duty belt guard

Components

- ✓ ASME safety valves
- ✓ Pressure gauge
- ✓ Intake filter/silencer
- ✓ Tank shut-off valve



AES-23315-120HM

HORIZONTAL MODELS

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	DIMENSIONS (LxWxH)	BOLT DOWN (LxW)	SHIP WT.	NET WT.
ACS-23105-80HM	18.0 @ 175	5.0 HP, 230V, 1Ø, 23.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	52x26.5x53in.	20.75x23.5in.	615 lb.	544 lb.
ACS-23175-80HM	23.5 @ 175	7.5 HP, 230V, 1Ø, 31.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	52x26.5x53in.	20.75x23.5in.	780 lb.	709 lb.
ADS-23110-120HM	34.2 @ 175	10.0 HP, 230V, 1Ø, 39.0A	Two stage	Cast iron	Splash lubricated cast iron	120-gallon	74x26.5x58in.	34.5x23.5in.	890 lb.	811 lb.
AES-23315-120HM	46.5 @ 175	15.0 HP, 230V, 3Ø, 38.0A	Two stage	Cast iron	Splash lubricated cast iron	120-gallon	74x26.5x58in.	34.5x23.5in.	935 lb.	856 lb.

VERTICAL MODELS

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	DIMENSIONS (LxWxH)	BOLT DOWN (LxW)	SHIP WT.	NET WT.
ACS-23105-80VM	18.0 @ 175	5.0 HP, 230V, 1Ø, 23.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	33x25x73in.	15.63x15.63in.	695 lb.	544 lb.
ACS-23175-80VM	23.5 @ 175	7.5 HP, 230V, 1Ø, 31.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	33x25x73in.	15.63x15.63in.	780 lb.	709 lb.

Consult factory for availability of more M Series air compressor models and voltages.